

AC current clamp specifications

	i5s	i200	i200s	i400	i400s	i800	i1000s	i3000s
AC range	10 mA to 6 A	1 A to 200 A	1 A to 200 A	1 A to 400 A	0.5 A to 400 A	0.1 A to 600 A	0.2 A to 1000 A	1 A to 3000 A
Accuracy	10 mA to 1 A 1% + 5 mA 1 A to 5 A 1%, 48 Hz to 65 Hz	≤ 3% +0.5 A 48 Hz to 65 Hz	≤ 1% +0.5 A 48 Hz to 65 Hz	2% + 0.06 A 45 Hz to 400 Hz	.5 A to 40 A, 2% + .015 A, 5 A to 400 A, 2% + .04 A, 45 Hz to 400 Hz	± 2% of rdg., 50 Hz to 1 kHz ± 3% of rdg., (typical) 30 Hz to 50 Hz and 1 kHz to 10 kHz	0.2 to 10 A: 3% + 0.1 A 10 A to 100 A: 2% + 0.5 A 100 A to 1000 A: 1% + 1 A 48 Hz to 65 Hz	1 A to 30 A: 2% + 0.1 A 1 A to 300 A: 2% + 0.5 A 1 A to 3000 A: 2% + 2 A 48 Hz to 65 Hz
Bandwidth (-3 dB)	40 Hz to 5 kHz	40 Hz to 40 kHz	40 Hz to 40 kHz	5 kHz to 20 kHz	5 Hz to 10 kHz	30 Hz to 10 kHz	5 Hz to 100 kHz	10 Hz to 100 kHz
Maximum conductor dia.	15 mm (0.59 in)	20 mm (0.8 in)	20 mm (0.8 in)	32 mm (1.25 in)	32 mm (1.25 in)	54 mm (2.13 in)	54 mm (2.13 in)	64 x 100 mm (2.52 in x 3.94 in)
Maximum conductor size	2 AWG	300 MCM	300 MCM	750 MCM	750 MCM	2-500 MCM or 1-1000 MCM	2-500 MCM or 1-1000 MCM	64 mm (2.52 in)
Output levels	400 mV/A	1 mA/A	10 mV/A 100 mV/A	1 mA/A	10 mV/A 1 mV/A	1 mA/A	1 mV/A 10 mV/A 100 mV/A	10 mV/A 1 mV/A 0.1 mV/A
Output cable	2.5 m to BNC termination	1.5 m shrouded banana plugs	2 m to BNC termination	1.5 m shrouded banana plugs	2.5 m to BNC termination	1.6 m shrouded banana plugs	1.6 m to BNC termination	2.1 m to BNC termination
Warranty	One-year	One-year	One-year	One-year	One-year	One-year	One-year	One-year
Safety rating	NA	CAT III 600 V	CAT III 600 V	CAT III 1000 V CAT IV 600 V	CAT III 1000 V CAT IV 600 V	CAT III 600 V	CAT III 600 V	CAT III 600 V

	i430-flex	i2000 flex	i3000s flex-24/i3000s flex-36	i6000s flex-24/i6000s flex-36
AC range	30 A to 3000 A	2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
Accuracy	± 1% of reading at 25 °C, 50 Hz	± 1% of range 45 Hz to 65 Hz Ranges: 20 A, 200 A, 2000 A	± 1% of range, 45 Hz to 65 Hz, Ranges: 30 A, 300 A, 3000 A	± 1% of range, 45 Hz to 65 Hz, Ranges: 60 A, 600 A, 6000 A
Bandwidth (-3 dB)	10 Hz to 7 kHz	10 Hz to 20 kHz	10 Hz to 50 kHz	10 Hz to 50 kHz
Maximum conductor dia.	177 mm (7 in)	177 mm (7 in)	177 mm (7 in) or 265 mm (10.4 in)	177 mm (7 in) or 265 mm (10.4 in)
Maximum conductor size	610 mm (24 in) circumference	610 mm (24 in) circumference	610 mm (24 in) circumference	610 mm (24 in) circumference
Output levels	85 mV at 1000 A rms, 50 Hz	100 mV/A, 10 mV/A, 1 mV/A	100 mV/A, 10 mV/A, 1 mV/A	50 mV/A, 5 mV/A, 0.5 mV/A
Output cable	2.5 m to BNC termination	2 m with double shrouded banana plugs	2.1 m to BNC termination	2 m to BNC termination
Battery life	No battery	NA	400 hours	400 hours
Warranty	One-year	One-year	One-year	One-year
Safety rating	CAT II 1000 V, CAT III 600 V, CAT IV 300 V	CAT III 600 V	CAT III 600 V	CAT III 600 V

AC clamp-on current probe compatibility

Model number	i5s	i200	i200s	i400	i400s	i800	i1000s	i3000s	i430-flex	i2000 FLEX ¹	i3000s FLEX	i6000s FLEX ³
10/11/12/12B/16/18			1 A to 200 A		1 A to 400 A*		0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
110/111/112			3 A to 200 A		30 A to 400 A*		3 A to 1000 A*	30 A to 3000 A		3 A to 2000 A	3 A to 3000 A	6 A to 6000 A
114/116			1 A to 200 A		0.6 A to 400 A*		0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
115/117		60 A to 200 A	1 A to 200 A	60 A to 400 A	0.6 A to 400 A*	60 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
21/23/73/75/77 Series III		1 A to 200 A	1 A to 200 A	1 A to 400 A	1 A to 400 A*	0.1 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
26/79 Series III		1 A to 40 A	1 A to 200 A	1 A to 40 A/ 200 A to 400 A	2 A to 400 A*	0.4 A to 40 A, 200 A to 800 A	0.2 A to 1000 A*	2 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
27		1 A to 200 A	1 A to 200 A	1 A to 400 A	1 A to 400 A*	0.1 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
70 Series III			1 A to 200 A		1 A to 400 A*		0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
77-IV						0.1 A to 800 A						6 A to 6000 A
175/177/179		3 A to 200 A	1 A to 200 A	3 A to 400 A	1 A to 400 A*	3 A to 800 A	0.3 A to 1000 A*	3 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
1577/1587		3 A to 200 A	1 A to 200 A	3 A to 400 A	3 A to 400 A*	3 A to 800 A	0.3 A to 1000 A*	3 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
83III/83V/88V		2 A to 200 A	1 A to 200 A	2 A to 400 A	1 A to 400 A*	0.25 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
85/87 Series III 87 Series V		2 A to 200 A	1 A to 200 A	2 A to 400 A	2 A to 400 A*	2 A to 800 A	0.2 A to 1000 A*	2 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
87/89 Series IV 187/189		2.5 A to 200 A	1 A to 200 A	2.5 A to 400 A	0.5 A to 400 A*	2.5 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
287/289		1 A to 200 A	1 A to 200 A	1 A to 400 A	0.5 A to 400 A*	1 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	
8060A/8062A		2 A to 200 A	1 A to 200 A	2 A to 400A	2 A to 400 A*	2 A to 800 A	0.2 A to 1000 A*	2 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
860 Series		1 A to 200 A	1 A to 200 A	1 A to 400 A	3 A to 400 A*	1.5 A to 800 A	0.3 A to 1000 A*	3 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
39/41B			1 A to 200 A ¹		1 A to 400 A ¹		0.2 A to 1000 A ¹	1 A to 3000 A ²		2 A to 2000 A ²	3 A to 3000 A ²	6 A to 6000 A
43B			1 A to 200 A		0.5 A to 400 A		0.2 A to 1000 A	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
434/435	10 mA to 6 A		1 A to 200 A		1.2 A to 400 A		0.3 A to 1000 A	1.2 A to 3000 A	30 A to 3000 A	Best to use i430Flex	Best to use i430Flex	
9X Series			1 A to 200 A		1 A to 400 A		0.2 A to 1000 A	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
120 Series			1 A to 200 A		2.5 A to 400 A		0.25 A to 1000 A	2.5 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
190 Series			1 A to 200 A		1 A to 400 A		0.2 A to 1000 A	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
45 DMM		1.5 A to 100 A	1 A to 200 A	1.5 A to 100 A	1.5 A to 400 A*	1.5 A to 100 A, 500 A to 800 A	0.15 A to 1000 A*	1.5 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
8808A		1 A to 200 A	1 A to 200 A	1 A to 400 A	0.5 A to 400 A*	1 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
8845A/8846A		1 A to 200 A	1 A to 200 A	1 A to 400 A	1 A to 400 A*	0.5 A to 800 A	0.2 A to 1000 A*	1 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
74X Series			1.1 A to 200 A		11 A to 400 A*		1.1 A to 1000 A*	11 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A
787/789		50 A to 200 A	1 A to 200 A	50 A to 400 A	2 A to 400 A*	50 A to 440 A	0.2 A to 1000 A*	2 A to 3000 A		2 A to 2000 A	3 A to 3000 A	6 A to 6000 A

*Requires PM9081/001 Adapters. ¹Three range version. ²Current and watt readings will be multiples of 10 higher or lower than actual on some ranges.
³Current readings will read half of the expected cardinal value on all meters.

AC/DC current clamp specifications

	i30	i30s	i50s	80i-110s	i310s	i410	i1010
DC range	30 mA to 30 A	30 mA to 30 A	30 mA to 30 A	0.1 A to 100 A	0.1 A to 450 A	1 A to 400 A	1 A to 1000 A
AC range	30 mA to 20 A rms	30 mA to 20 A rms	30 mA to 30 A rms	0.1 A to 70 A	0.1 A to 300 A	1 A to 400 A	1 A to 600 A
Accuracy	± 1 % of reading, ± 2 mA	± 1 % of reading, ± 2 mA	± 0.5 % at In typical, ± 1.5 % at 1 max	0.1 A to 10 A; dc to 1 kHz: ± 3 % + 50 mA; up to 100 A add 15 %; up to 20 kHz add 12 %	30 A range: 1 % + 50 mA 300 A range: 1 % + 300 mA	3.5 % + 0.5 A for dc or ac (45 Hz to 400 Hz)	2 % + 0.5 A for dc or ac (45 Hz to 400 Hz)
Bandwidth (-3 dB)	dc to 20 kHz (-0.5 dB)	dc to 100 kHz (-0.5 dB)	dc to 50 MHz (-3 dB)	100 kHz	dc to 20 kHz	3 kHz	10 kHz
Zero error adjustment	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Maximum conductor diameter	19 mm (0.75 in)	19 mm (0.75 in)	5 mm x 5 mm (0.20 in x 0.20 in)	11.8 mm (0.46 in)	19 mm (0.75 in)	30 mm (1.18 in)	30 mm (1.18 in)
Maximum conductor size	250 MCM	250 MCM	NA	1 AWG	250 MCM	750 MCM or 2-500 MCM	750 MCM or 2-500 MCM
Output levels	100 mV/A	100 mV/A	1 V/A, 100 mV/A	10 mV/A, 100 mV/A	10 mV/A, 100 mV/A	1 mV/A	1 mV/A
Output cable	1.5 meter with shrouded dual banana plug	2 meter with BNC termination	2 meter with BNC termination	1.6 meter with BNC termination	2 meters with BNC termination and a BNC to safety shrouded banana adapter	1.2 meter with shrouded banana plugs	1.2 meter with shrouded banana plugs
Battery life (hours)	30	30	± 12 V @ 550 mA (Power supply)	40	30	60	60
Warranty	One-year	One-year	One-year	One-year	One-year	One-year	One-year
Safety	CAT III 300 V	CAT III 300 V	CAT I 300 V, CAT II 150 V	CAT II 600 V; CAT III 300 V	CAT III 300 V	CAT III 600 V	CAT III 600 V

AC/DC clamp-on current probe compatibility

Model number	80i-110s	i410	i1010	i30	i30s	i310s	i50s
10/11/12/12B/16/18	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	5 A to 400 A dc/ 7 A to 400 A ac	5 A to 1000 A dc/ 7 A to 600 A ac	40 mA to 30 A dc/ 60 mA to 20 A ac	40 mA to 30 A dc/ 60 mA to 20 A ac	0.4 A to 450 A dc/ 0.6 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
110/111/112	0.14 A to 100 A dc/ 3 A to 70 A ac*	5 A to 400 A dc/ 300 A to 400 A ac	5 A to 1000 A dc/ 300 A to 600 A ac	40 mA to 30 A dc/ 3 A to 20 A ac	40 mA to 30 A dc/ 3 A to 20 A ac	0.4 A to 450 A dc/ 30 A to 300 A ac	30 mA to 30 A dc and 300 mA to 30 A ac*
114/115/116/117	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1.4 A to 400 A dc/ 6 A to 400 A ac	1.4 A to 1000 A dc/ 6 A to 600 A ac	30 mA to 30 A dc/ 60 mA to 20 A ac	30 mA to 30 A dc/ 60 mA to 20 A ac	0.1 A to 450 A dc/ 0.6 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
21/23/70/73/75/77 Series III	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 5 A to 400 A ac	1 A to 1000 A dc/ 5 A to 600 A ac	30 mA to 30 A dc/ 40 mA to 20 A ac	30 mA to 30 A dc/ 40 mA to 20 A ac	0.1 A to 450 A dc/ 0.4 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
26/79 Series III	0.1 A to 100 A dc/ 0.2 A to 70 A ac*	1 A to 400 A dc/ 20 A to 400 A ac	1 A to 1000 A dc/ 20 A to 600 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	0.1 A to 450 A dc/ 2 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
27	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 1 A to 400 A ac	1 A to 1000 A dc/ 1 A to 600 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	0.1 A to 450 A dc/ 0.1 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
77-IV	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 5 A to 400 A ac	1 A to 1000 A dc/ 5 A to 600 A ac	30 mA to 30 A dc/ 40 mA to 20 A ac	30 mA to 30 A dc/ 40 mA to 20 A ac	0.1 A to 450 A dc/ 0.4 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
175/177/179	0.11 A to 100 A dc/ 0.3 A to 70 A ac*	1.6 A to 400 A dc/ 30 A to 400 A ac	1.6 A to 1000 A dc/ 30 A to 600 A ac	30 mA to 30 A dc/ 300 mA to 20 A ac	30 mA to 30 A dc/ 300 mA to 20 A ac	0.1 A to 450 A dc/ 3 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
1577/1587	0.1 A to 100 A dc/ 0.3 A to 70 A ac*	1.2 A to 400 A dc/ 30 A to 400 A ac	1.2 A to 1000 A dc/ 30 A to 600 A ac	30 mA to 30 A dc/ 300 mA to 20 A ac	30 mA to 30 A dc/ 300 mA to 20 A ac	0.1 A to 450 A dc/ 3 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
83-III/83-V/88-V	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 1 A to 400 A ac	1 A to 1000 A dc/ 1 A to 600 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	0.1 A to 450 A dc/ 0.1 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
85-III/87-III/87-V	0.1 A to 100 A dc/ 0.2 A to 70 A ac*	1 A to 400 A dc/ 20 A to 400 A ac	1 A to 1000 A dc/ 20 A to 600 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	0.1 A to 450 A dc/ 2 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
87-IV/89-IV/187/189	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 2.5 A to 400 A ac	1 A to 1000 A dc/ 2.5 A to 600 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	0.1 A to 450 A dc/ 0.25 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
287/289	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 1 A to 400 A ac	1 A to 1000 A dc/ 1 A to 600 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	0.1 A to 450 A dc/ 0.1 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
8060A/8062A	0.1 A to 100 A dc/ 0.2 A to 70 A ac*	1 A to 400 A dc/ 20 A to 400 A ac	1 A to 1000 A dc/ 20 A to 600 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	0.1 A to 450 A dc/ 2 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
860 Series	0.1 A to 100 A dc/ 0.3 A to 70 A ac*	1 A to 400 A dc/ 30 A to 400 A ac	1 A to 1000 A dc/ 30 A to 600 A ac	30 mA to 30 A dc/ 300 mA to 20 A ac	30 mA to 30 A dc/ 300 mA to 20 A ac	0.1 A to 450 A dc/ 3 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
39/41B	Usable but will read 10 or 100 times higher	1 A to 400 A ac** Not spec'd for dc	1 A to 600 A ac** Not spec'd for dc	Usable but will read 100 times higher**	Usable but will read 100 times higher	Not spec'd for dc 0.6 A to 300 A ac	Usable but will read 100 or 1000 times higher, ac only
9X Series	0.1 A to 100 A dc/ 0.1 A to 70 A ac	1 A to 400 A dc/ 5 A to 400 A ac**	1 A to 1000 A dc/ 5 A to 600 A ac**	30 mA to 30 A dc/ 50 mA to 20 A ac**	30 mA to 30 A dc/ 50 mA to 20 A ac	0.1 A to 450 A dc/ 0.5 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac
120 Series	0.1 A to 100 A dc/ 0.25 A to 70 A ac	1 A to 400 A dc/ 25 A to 400 A ac**	1 A to 1000 A dc/ 25 A to 600 A ac**	30 mA to 30 A dc/ 250 mA to 20 A ac**	30 mA to 30 A dc/ 250 mA to 20 A ac	0.1 A to 450 A dc/ 2.5 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac
190 Series	0.1 A to 100 A dc/ 0.1 A to 70 A ac	1 A to 400 A dc/ 5 A to 400 A ac**	1 A to 1000 A dc/ 5 A to 600 A ac**	30 mA to 30 A dc/ 50 mA to 20 A ac**	30 mA to 30 A dc/ 50 mA to 20 A ac	0.1 A to 450 A dc/ 0.5 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac
45 DMM	0.1 A to 100 A dc/ 0.15 A to 70 A ac*	1 A to 400 A dc/ 15 A to 400 A ac	1 A to 1000 A dc/ 15 A to 600 A ac	30 mA to 30 A dc 150 mA to 20 A ac	30 mA to 30 A dc 150 mA to 20 A ac	0.1 A to 450 A dc/ 1.5 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
8808A	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 2 A to 400 A ac	1 A to 1000 A dc/ 2 A to 600 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	0.1 A to 450 A dc/ 0.2 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
8845A/8846A	0.1 A to 100 A dc/ 0.1 A to 70 A ac*	1 A to 400 A dc/ 1 A to 400 A ac	1 A to 1000 A dc/ 1 A to 600 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	30 mA to 30 A dc/ 30 mA to 20 A ac	0.1 A to 450 A dc/ 1 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*
705/707	0.1 A to 100 A dc, no ac*	4 A to 400 A dc, no ac	4 A to 1000 A dc, no ac	40 mA to 30 A dc, no ac	40 mA to 30 A dc, no ac	0.4 A to 450 A dc, no ac	30 mA to 30 A dc, no ac*
715	0.1 A to 100 A dc, no ac*	4 A to 400 A dc, no ac	4 A to 1000 A dc, no ac	40 mA to 30 A dc, no ac	40 mA to 30 A dc, no ac	0.1 A to 450 A dc, no ac	30 mA to 30 A dc, no ac*
74X Series	0.1 A to 100 A dc/ 1.1 A to 70 A ac*	1 A to 400 A dc/ 110 A to 400 A ac	1 A to 1000 A dc/ 110 A to 600 A ac	30 mA to 30 A dc/ 1.1 A to 20 A ac	30 mA to 30 A dc/ 1.1 A to 20 A ac	0.1 A to 450 A dc/ 11 A to 300 A ac	30 mA to 30 A dc and 110 mA to 30 A ac*
787/789	0.1 A to 100 A dc/ 0.2 A to 70 A ac*	1 A to 400 A dc/ 20 A to 400 A ac	1 A to 1000 A dc/ 20 A to 600 A ac	30 mA to 30 A dc/ 200 mA to 20 A ac	3 mA to 30 A dc/ 200 mA to 20 A ac	0.1 A to 450 A dc/ 2 A to 300 A ac	30 mA to 30 A dc and 30 mA to 30 A ac*

*Requires PM9081/001 Adapters. **Requires PM9082/001 Adapter