

## Fluke 1730 Firmware 1.1 Release Notes

- Improvements:
- Aux configuration in Measurement Configuration added
- Japanese language added
- Additional keyboard input methods depending on display language:
  - Chinese - Input method: Pinyin
  - Japanese - Input methods: Hiragana, Katagana and Kanji
  - Korean - Hangul keyboard layout
  - Russian - Russian keyboard layout
- Virtual keyboard: Additional symbols accessible with Shift key
- Support for non-Latin session file names added
- Synchronize with PC clock (requires FEA V1.1)
- Additional screens for Live Power added.
- Use F4 - Show Menu to select from the list of available screens
- Energy is now available without starting a logging session.
- In Live Power use F4 - Show Menu to select kVAh, kWh or kvar.
- Download screenshots to Energy Analyze via USB cable
- Delete logging sessions and screenshots remotely from
- Energy Analyze via USB cable
- Add a warning to confirm when stopping a logging session
- Logging duration can be configured in hours or days.
- Set-up of logging session start and end date and time added
- Topologies 3 phase high leg delta and 3 phase delta balanced added.
- A power off resets now the phase mapping and current direction to defaults.

### Bugfix:

- Show P-P chart in 3ph Delta configuration. P-N was shown instead in V1.0.